



TEGERA® 8145

Chemical protection glove, 0,33 mm latex, diamond grip pattern, flock-lined, Cat. III, yellow, phthalate-free, waterproof, for allround work

PROPERTIES

Extra flexible, good grip, comfortable

SPECIFICATION

TYPE OF GLOVE Chemical protection gloves

CATEGORY Cat. III

SIZE RANGE (EU) 7, 8, 9, 10

DIPPING MATERIAL Latex

THICKNESS 0,33 mm

INSIDE Flock-lined

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 300 mm

COLOUR Yellow

PAIRS PER PACKAGE/CARTON 10/100

PIECES PER BOX 0

DISPLAY Bag with euro slot

OUTER MATERIAL SPECIFICATION Natural latex

INNER MATERIAL SPECIFICATION Cotton

SIZE	ART. NO.	EAN NO.
7	8145-7	7392626033993
8	8145-8	7392626034006
9	8145-9	7392626034013
10	8145-10	7392626034020

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8145

FEATURES

Approved for handling foodstuffs, phthalate-free, waterproof, elastic

PREVENTS RISK OF

Contact with moisture

PRIMARY ENVIRONMENTS OF USE

Wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Agricultural work, cleaning, foodstuff handling, hotel- and restaurant work, kitchen work, sanitation


PRIMARY INDUSTRIES OF USE


Agriculture, HoReCa, service

TYPE OF WORK

Medium weight

CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1000X  EN ISO 374-1:2016/Type C

 EN ISO 374-5:2016   

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-07-01

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8145

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	1	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	0	(4)
d) Puncturing resistance (N)	0	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)




EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms – Part 5 Terminology and performance requirements for microorganism risks.

EN ISO 374-1:2016/Type C Protective gloves against dangerous chemicals and microorganisms – Part 1: Terminology and performance requirements for chemical



CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1000X  EN ISO 374-1:2016/Type C

 EN ISO 374-5:2016  LATEX 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-07-01

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8145

Test according to EN ISO 374-1:2016

Tested chemical	K
Permeation level	2
Degradation %	1,3

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480





Definition of breakthrough time through the glove palm (Lugm/cm²/min)

K: Sodium hydroxide 40% (CAS number 1310-73-2) risks.



CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1000X  EN ISO 374-1:2016/Type C

 EN ISO 374-5:2016   

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-07-01

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com