



AQUATHAN®



Thinsulate
INSULATION

SIZE	ART. NO.	EAN NO.
7	191-7	7340118354927
8	191-8	7340118355047
9	191-9	7340118301457
10	191-10	7392626075979
11	191-11	7340118301396
12	191-12	7340118301419

TEGERA® 191

Leather glove, winter-lined, full grain cowhide of top quality, Thinsulate™ 200g, Cat. II, black, white, reinforced thumb, waterproof, string lock, for allround work

PROPERTIES

Good fingertip sensitivity, flexible, durable, good grip, perfect fit, extremely warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain cowhide of top quality

BACK MATERIAL Full grain cowhide of top quality

LINING Winter-lined

LINING MATERIAL Thinsulate™ 200g

CLO 3,3 m²·K/W

DEXTERITY 2

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

FASTENING String lock

LENGTH RANGE 342-396 mm

COLOUR Black, White

PAIRS PER PACKAGE/CARTON 3/30

PIECES PER BOX 0

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather, polyester, natural latex

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 191

FEATURES

Extra long, reinforced thumb, waterproof

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, cold environments, wet environments, moist environments, harsh environments

PRIMARY AREAS OF USE

Fishing, fishing industry work, hunting, marine work, military work, warehouse work

PRIMARY INDUSTRIES OF USE

Transportation, building and construction, logistics

TYPE OF WORK

Medium weight

2(3)

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2232X



EN 511:2006
331

EN 511 cl. 5.2
Flexibility behavior (-20°C): Pass

EN 511 cl. 5.4
Extreme cold flexibility (-50°C): Pass



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 191

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2232X



EN 511:2006
331

EN 511 cl. 5.2

Flexibility behavior (-20°C): Pass

EN 511 cl. 5.4

Extreme cold flexibility (-50°C): Pass



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com