

**jalas**<sup>®</sup> GRAN PREMIO 1848K TITAN

EN ISO 20345:2011 S3, SRC, HRO, CI, HI ASTM F2413-18 M/I/C SD 35 PR



Learn more

A mid-cut safety boot with Thinsulate™ heat-resistant lining for highest (S3) protection for tough work. The PU-coated leather upper with Kevlar® seams resists heat of up to 204° C for extended periods of time. The oil and heat-resistant nitrile outer sole gives excellent grip and JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD® help prevent injuries.

**CHARACTERISTICS**

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

**FUNCTIONS**

- ProNose toe reinforcement
- Thinsulate™ heat insulation
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Ventilating insole
- Pull loops
- Water repellent
- Double shock absorption zones



**PREVENTS RISK OF**

toe injuries, nail penetration, antistatic

**PRIMARY ENVIRONMENTS OF USE**

outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration

**PRIMARY AREAS OF USE**

sheet-metal work, welding, hot work, mining

**PRIMARY INDUSTRIES OF USE**

metal fabrication

**SPECIFICATION**

TYPE Safety footwear, Boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Wide

COLLECTION GRAN PREMIO

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, Cambrelle®, Thinsulate™

INSOLE FX2 Pro

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Hook-and-loop

COLOUR Black


NET WEIGHT, (SIZE 42) 1,39 kg

**COMPLIANCE**



EN ISO 20345:2011  
S3, SRC, HRO, CI, HI

ASTM F2413-18  
M/I/C  
SD 35 PR



**FEATURES**



Anti-static properties



Ergothon Shock Absorption System



Heat-resistant upper



Aluminium toecap



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Water repellent

SIZE	ARTICLE NUMBER	EAN
35	1848K-35	6408487506505
36	1848K-36	6408487502330
37	1848K-37	6408487502347
38	1848K-38	6408487502354
39	1848K-39	6408487502361
40	1848K-40	6408487502378
41	1848K-41	6408487502385
42	1848K-42	6408487502392
43	1848K-43	6408487502408
44	1848K-44	6408487502415
45	1848K-45	6408487502422
46	1848K-46	6408487502439
47	1848K-47	6408487502446
48	1848K-48	6408487502453
49	1848K-49	6408487506512
50	1848K-50	6408487506529

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com