



TEGERA® 9180

Anti-vibration glove, unlined, Microthan®, Vibrothan®, polyester, Cat. II, black, grey, yellow, reinforced index finger, reinforced fingertips, hook-and-loop, for heavy work

PROPERTIES

Flexible, good grip, good fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Anti-vibration gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

COLLECTION PRO

PALM MATERIAL Microthan®, Vibrothan®

BACK MATERIAL Polyester

LINING Unlined

DEXTERITY 5

FASTENING Hook-and-loop

LENGTH RANGE 210-242 mm

COLOUR Black, Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Polyurethane, natural latex, nylon, polyester

MicroThan®

VIBROTHAN®

SIZE	ART. NO.	EAN NO.
7	9180-7	7392626033498
8	9180-8	7392626033504
9	9180-9	7392626033511
10	9180-10	7392626033528
11	9180-11	7392626033535
12	9180-12	7392626036130

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9180

FEATURES

Vibration-reducing according to EN ISO 10819, chrome free, reinforced index finger, reinforced seams, reinforced fingertips, padded palm, pre-curved fingers, specially designed thumb, short model, ergonomically shaped, specially designed details

PREVENTS RISK OF

Chrome allergy, vibration injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY INDUSTRIES OF USE

Mining, machinery and equipment, MRO, automotive, building and construction

TYPE OF WORK

Heavy weight

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
0222X

EN ISO 10819:2013



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9180

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	0	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN ISO 10819:2013 Mechanical vibration and shock. Hand-arm vibration. Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand



CE Cat. II

EN 420:2003 + A1:2009



EN 388:2016 0222X

EN ISO 10819:2013



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.