



OGT™

TEGERA® 6615

Leather glove, unlined, full grain cowhide, Cat. II, grey, water and oil repellent, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, excellent grip in oily environments

SPECIFICATION

TYPE OF GLOVE All-round work gloves, Assembly gloves, Heavy duty gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain cowhide

BACK MATERIAL Full grain cowhide

LINING Unlined

DEXTERITY 5

FASTENING Elasticated 180°

COLOUR Grey

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

1(3)

TEGERA® 6615

FEATURES

Water and oil repellent

PREVENTS RISK OF

Prevents risk of, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with oil

PRIMARY ENVIRONMENTS OF USE

Slippery environments, oily and greasy environments

PRIMARY AREAS OF USE

Assembly, engineering, petro-chemical work

PRIMARY INDUSTRIES OF USE

Oil, gas, petrochemical, machinery and equipment, MRO, automotive

TYPE OF WORK

Medium weight

2(3)

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3011X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 6615

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3011X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com