



Thinsulate
INSULATION

SIZE	ART. NO.	EAN NO.
6	8151-6	7340118372761
7	8151-7	7340118372853
8	8151-8	7340118372945
9	8151-9	7340118373034
10	8151-10	7340118373126
11	8151-11	7340118373218
12	8151-12	7340118373300

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8151

Leather glove, fully lined, full grain goatskin of top quality, Thinsulate™ 40g, Cat. II, black, for touchscreen, water repellent leather, elasticated 180°, for allround work

PROPERTIES

Good fingertip sensitivity, extra flexible, good grip, perfect fit

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves, Special protection work gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

LINING Fully lined

LINING MATERIAL Thinsulate™ 40g

CLO 0,7 m²-K/W

DEXTERITY 5

FASTENING Elasticated 180°

COLOUR Black

PAIRS PER PACKAGE/CARTON 3/72

PAIRS PER HANGTAG 1

DISPLAY Hangtag with euro slot

OUTER MATERIAL SPECIFICATION Leather, elastane

INNER MATERIAL SPECIFICATION Polyester

TEGERA® 8151

FEATURES

For touchscreen, water repellent leather

PREVENTS RISK OF

Contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, cold environments

PRIMARY AREAS OF USE

Security- and police work

PRIMARY INDUSTRIES OF USE

Service

TYPE OF WORK

Medium weight

CE Cat. II

EN ISO 21420:2020



EN 388:2016+A1:2018
3121X



EN 511:2006
12X

EN ISO 11640:2018

TEGERA® 8151

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN ISO 21420:2020 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)		(4)
b) Cut resistance (Index)		(5)
c) Tear resistance (N)		(4)
d) Puncturing resistance (N)		(4)
e) Cut resistance, EN ISO 13997 (N)		(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN ISO 21420:2020



EN 388:2016+A1:2018
3121X



EN 511:2006
12X

EN ISO 11640:2018

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com