



TEGERA® 8805 INFINITY

Cut resistant glove, nitrile foam, waterbased PU, palm-dipped, foam grip pattern, cut resistance level B, 18 gg, carbon, CRF® Technology, nylon, stainless steel fibre yarn, Cat. II, grey, yellow, withstands contact heat up to 100°C, DMF (DMFa) free, anatomically designed, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip in oily environments, extra comfortable

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 9

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

COLLECTION Infinity

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, waterbased PU

LINING MATERIAL 18 gg, Carbon, CRF® Technology, Nylon, Stainless steel fibre yarn

DEXTERITY 5

GRIP PATTERN Foam grip pattern

CUFF STYLE Knitwrist cuff

COLOUR Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/120

PIECES PER BOX 0

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE, stainless steel fibre yarn, carbon thread, nylon

1(3)

INFINITY™



CRF®



EAN NO.

5	8805-5	7340118328089
6	8805-6	7340118319322
7	8805-7	7340118319339
8	8805-8	7340118319346
9	8805-9	7340118319353
10	8805-10	7340118319308
11	8805-11	7340118319315

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8805 INFINITY

FEATURES

Withstands contact heat up to 100°C, approved for handling foodstuffs, for touchscreen, anatomically designed

PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

Dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, engineering, fine assembly, glass industry work, HVAC installation, installation work, machine driving, machine operating, metalwork, painting, paper industry work, repair work, service work, sheet-metal work, shop work, transport work, warehouse work





PRIMARY INDUSTRIES OF USE

Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

 Cat. II

 EN 420:2003 + A1:2009  EN 388:2016 4X41B  EN 407:2004 X1XXXX 



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-07

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8805 INFINITY

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

ANSI/ISEA 105-2016 Cut resistance according to the American National Standard Institute 105-2016. Levels A1-A9

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)


EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-07

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com