



MicroThan®+



SIZE	ART. NO.	EAN NO.
8	9190-8	7392626030541
9	9190-9	7392626030558
10	9190-10	7392626030565
11	9190-11	7392626030572

## TEGERA® 9190

Synthetic leather glove, winter-lined, Microthan®+, diamond grip pattern, polyester, fleece, Cat. II, black, grey, yellow, wrist support, hook-and-loop, for allround work

### PROPERTIES

Flexible, excellent grip, perfect fit, extra comfortable

### SPECIFICATION

TYPE OF GLOVE All-round work gloves, Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

COLLECTION PRO

PALM MATERIAL Microthan®+

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

FASTENING Hook-and-loop

LENGTH RANGE 255-280 mm

COLOUR Black, Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Acrylic

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 9190

### FEATURES

Wrist-supporting, extra long, chrome free, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, water repellent, moisture resistant, ergonomically shaped, reflector, specially designed details

### PREVENTS RISK OF

Chrome allergy, wrist injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Dark environments, slippery environments, dry environments, cold environments, moist environments, dirty environments

### PRIMARY AREAS OF USE

Airport work, building and construction, carpentry, construction, engineering, installation work, machine driving, machine operating, mining, soil preparation, transport work, warehouse work



### PRIMARY INDUSTRIES OF USE


Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003 + A1:2009  EN 388:2016 2222X  EN 511:2006 21X

EN 511 cl. 5.2 Flexibility behavior (-20°C): Pass 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

2(3)

  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

# TEGERA® 9190

## EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

## COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

## EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

## EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
2222X



EN 511:2006  
21X

EN 511 cl. 5.2

Flexibility behavior (-20°C): Pass



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com