

TEGERA® 9181

Anti-vibration glove, unlined, full grain goatskin of top quality, Vibrothan®, Cat. II, black, yellow, reinforced index finger, reinforced seams, hook-and-loop, for heavy work

PROPERTIES

Very durable, comfortable

SPECIFICATION

TYPE OF GLOVE Anti-vibration gloves

CATEGORY Cat. II

SIZE RANGE (EU) 9, 10, 11

COLLECTION PRO

PALM MATERIAL Full grain goatskin of top quality, Vibrothan®

BACK MATERIAL Full grain goatskin of top quality

LINING Unlined

FASTENING Hook-and-loop

LENGTH RANGE 240-260 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/36

PIECES PER BOX 0

DISPLAY No thread

OUTER MATERIAL SPECIFICATION Leather, natural latex, polyurethane



VIBROTHAN®

SIZE	ART. NO.	EAN NO.
9	9181-9	7392626059351
10	9181-10	7392626055919
11	9181-11	7392626055926

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9181

FEATURES

Vibration-reducing according to EN ISO 10819, reinforced index finger, padded palm, pre-curved fingers, short model

PREVENTS RISK OF

Vibration injuries

PRIMARY ENVIRONMENTS OF USE

Harsh environments


PRIMARY INDUSTRIES OF USE

Mining, machinery and equipment, MRO, automotive, building and construction

TYPE OF WORK

Heavy weight

CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3121X EN ISO 10819:2013

EN ISO 11640:2012 Dry 150 cycles 4/5 Wet 50 cycles 3/4  

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9181

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	


Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN ISO 10819:2013 Mechanical vibration and shock. Hand-arm vibration. Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3121X EN ISO 10819:2013

EN ISO 11640:2012  
Dry 150 cycles 4/5 Wet 50 cycles 3/4

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.