





•jalas EXALTER 9988 GTX

EN ISO 20345:2011 S3, SRC, WR, HRO ASTM F2413-18 M/I/C SD 35 PR



Learn more

A MID-CUT SAFETY SHOE, NOW WITH GORE-TEX

A light, comfortable, safety shoe with side-mounted BOA®. Waterproof due to GORE-TEX. Its Microfiber upper and sock-like construction provides great comfort and fit and has anti-static properties. The nitrile outer sole is heat and oil resistant for outstanding grip. It features also our JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®.

CHARACTERISTICS

- Perfect fit
- Extra comfortable
- Excellent shock absorption
- High level of protection
- Excellent grip

FUNCTIONS

- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Waterproof
- Specially designed details
- Double shock absorption zones
- Polstered shaft edge
- Ventilating insole
- BOA® Fit System
- Conforms with IEC 61340-5-1 (ESD)
- Ergonomically shaped
- Quick-tie
- Stabilizator

- Soft
- Free from animal-derived materials
- GORE-TEX Performance Comfort Footwear technology







PREVENTS RISK OF

toe injuries, nail penetration, sprain injuries, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

outdoors, all-year use, environments with risk for outsole penetration, wet environments, moist environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite
(PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

INSOLE FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA,

Polyester-based conductive thread, Neo foam, Poron®

XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING **BOA** Fit System

COLOUR Black

NET WEIGHT, (SIZE 42) 1,16 kg

COMPLIANCE





EN ISO 20345:2011 S3, SRC, WR, HRO

ASTM F2413-18 M/I/C SD 35 PR





FEATURES



Anti-static properties



Ergothan Shock Absorption System



ESD





Oil-resistant outsole



Heat-resistant outsole







Stabilizator

SIZE	ARTICLE NUMBER	EAN
34	9988-34	6408487534324
35	9988-35	6408487534362
36	9988-36	6408487534409
37	9988-37	6408487534447
38	9988-38	6408487534485
39	9988-39	6408487534522
40	9988-40	6408487534560
41	9988-41	6408487534607
42	9988-42	6408487534645
43	9988-43	6408487534683
44	9988-44	6408487534720
45	9988-45	6408487534768
46	9988-46	6408487534805
47	9988-47	6408487534843



 $Limav \"{a}gen~28, SE-793~32~Leks and, Sweden~Phone~46~(0)~247~360~00~|~info@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~order@ejendals.com~|~$