

TEGERA® 74

Cut sleeve, cut resistance level B, 13 gg, KEVLAR® fiber, spandex, stainless steel fibre yarn, Cat. II, yellow, withstands contact heat up to 100°C, approved for handling foodstuffs, bulk pack, elasticated 360°, for allround work

PROPERTIES

High level of protection, flexible, durable, perfect fit, comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant sleeves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 9.6

SIZE RANGE (EU) 7, 8, 9, 10

LINING MATERIAL 13 gg, KEVLAR® fiber, Spandex, Stainless steel fibre yarn

FASTENING Elasticated 360°

LENGTH RANGE 420-490 mm

COLOUR Yellow

PIECES PER PACKAGE/CARTON 6/60

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION Para-aramid, elastane, stainless steel fibre yarn



SIZE	ART. NO.	EAN NO.
7	74-7	7340118387741
8	74-8	7340118348681
9	74-9	7340118348773
10	74-10	7340118348865

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 74

FEATURES

Withstands contact heat up to 100°C, approved for handling foodstuffs

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments

PRIMARY AREAS OF USE

Assembly, building and construction, decontamination, engineering, glass industry work, inspection work, installation work, machine operating, metalwork, warehouse work

PRIMARY INDUSTRIES OF USE

Metal fabrication, machinery and equipment, MRO, automotive, transportation, building and construction, logistics

TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003 + A1:2009  EN 388:2016 2X4XB  EN 407:2020 No Flame Protection X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 74

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2020 Protective gloves and other hand protective equipments against thermal risks

Suitable for contact with foodstuffs



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X4XB



EN 407:2020 No Flame Protection
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com