



TEGERA® 11CVA

Welding and heat-resistant glove, full grain goatskin of top quality, Cat. III, white, yellow, reinforced seams, chrome free, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good fit

SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. III

SIZE RANGE (EU) 8, 10, 11

PALM MATERIAL Full grain goatskin of top quality

BACK MATERIAL Full grain goatskin of top quality

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 320-350 mm

COLOUR White, Yellow

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
10	11CVA-10	7340118312637
11	11CVA-11	7340118312651
8	11CVA-8	7340118312675

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 11CVA

FEATURES

Withstands contact heat up to 100°C, chrome-free tanning, reinforced seams, water repellent leather

PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Warm surfaces, dirty environments, harsh environments

PRIMARY AREAS OF USE

Engineering, hot work, metalwork, mining, welding

PRIMARY INDUSTRIES OF USE


Mining, oil, gas, petrochemical, metal fabrication, automotive

TYPE OF WORK

Light weight

 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3121X  EN 407:2004 412X4X EN 12477:2001 + A1:2005

Type B EN 1149-2:1997 R:0.38x10⁶Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-21


PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 11CVA

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders


Type B - Higher dexterity (with lower other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3121X  EN 407:2004 412X4X  EN 12477:2001 + A1:2005

Type B EN 1149-2:1997 R:0.38x10⁶Q 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-21

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com