

## TEGERA® 9128

Synthetic leather glove, winter-lined, Microthan®+, diamond grip pattern, polyester, fleece, Thinsulate™ 40g, Cat. II, black, yellow, high visibility colour, for touchscreen, waterproof, elasticated 360°, for allround work

### PROPERTIES

Flexible, durable, excellent grip, perfect fit, extra comfortable

### SPECIFICATION

TYPE OF GLOVE All-round work gloves, Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

COLLECTION PRO

PALM MATERIAL Microthan®+

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece, Thinsulate™ 40g

CLO 0,7 m²·K/W

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

FASTENING Elasticated 360°

LENGTH RANGE 240-275 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester



MicroThan®+

AQUATHAN®



Thinsulate™  
INSULATION

SIZE	ART. NO.	EAN NO.
6	9128-6	7340118354798
7	9128-7	7392626070868
8	9128-8	7392626070882
9	9128-9	7392626070905
10	9128-10	7392626070820
11	9128-11	7392626070844
12	9128-12	7340118354781

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 9128

### FEATURES

For touchscreen, chrome free, high visibility colour, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, knuckle protection, windproof, waterproof, ergonomically shaped, reflector, specially designed details

### PREVENTS RISK OF

Chrome allergy, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Dark environments, windy environments, slippery environments, dry environments, cold environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

### PRIMARY AREAS OF USE

Agricultural work, airport work, building and construction, carpentry, construction, engineering, forest work, gardening, machine driving, machine operating, repair work, soil preparation, transport work, warehouse work, wood industry work

### PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
1121X



EN 511:2006  
111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

# TEGERA® 9128

## EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

## COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	1	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

## EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
1121X



EN 511:2006  
111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com