



## TEGERA® 295

Leather glove, winter-lined, full grain goatskin, spandex, Thinsulate™ 40g, Cat. II, blue, grey, white, waterproof, elasticated 360°, for allround work

### PROPERTIES

Extremely good fingertip sensitivity, extra flexible, durable, good grip, perfect fit, extra comfortable, warm

### SPECIFICATION

TYPE OF GLOVE All-round work gloves, Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12, 13, 14, 15

PALM MATERIAL Full grain goatskin

BACK MATERIAL Spandex

LINING Winter-lined

LINING MATERIAL Thinsulate™ 40g

CLO 0,7 m<sup>2</sup>·K/W

DEXTERITY 5

FASTENING Elasticated 360°

COLOUR Blue, Grey, White

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather, elastane, polyester, natural latex

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester

AQUATHAN®



Thinsulate  
INSULATION

SIZE	ART. NO.	EAN NO.
6	295-6	7340118313061
7	295-7	7340118313092
8	295-8	7392626034181
9	295-9	7392626034198
10	295-10	7392626034204
11	295-11	7392626034211
12	295-12	7392626037281
13	295-13	7340118343785
14	295-14	7340118327099
15	295-15	7340118327211

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 295

### FEATURES

Reinforced fingers and thumb, waterproof

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Cold environments, wet environments

### PRIMARY AREAS OF USE

Airport work, building and construction, carpentry, machine driving, machine operating, repair work, transport work

### PRIMARY INDUSTRIES OF USE

Transportation, utilities, building and construction, logistics

### TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
2121X



EN 511:2006  
121



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

[info@ejendals.com](mailto:info@ejendals.com)

[order@ejendals.com](mailto:order@ejendals.com)

[www.ejendals.com](http://www.ejendals.com)

## TEGERA® 295

### EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07  
France

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

### EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

### EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
2121X



EN 511:2006  
121



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-19

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com